

# VERSA Coater™ PHOTOMATE—UV COATER AND PHOTO TEXTURING SYSTEM



## DRYTAC®

**EXPERTS IN FINISHING SOLUTIONS**

### FEATURES

- Available in 432mm (17"), 610mm (24") and 915mm (36") formats
- Sensor activated light shield
- Standard processing speeds up to 30 metres (100 feet)/minute
- Handles cut sheet flexible or rigid coated media up to 12mm thick on the bottom smooth roller and up to 300gsm (0.35mm thickness) on the top textured roller.
- Patented, engraved roller system creates Smooth, Artisan, Fine Canvas, Artisan, Leather or Linen textures\*
- Optional proofing roller to watermark proofs
- Variable coating thickness from 8 to 14 microns
- Advanced design elliptical reflector
- Monitored lamp control
- Multi-tank coating carousel
- Enclosed conveyor for dry, dust-free prints
- Automated start-up and shut-down
- Filtered recirculation system to maximize coating mileage
- Optional feeder and jogger available
- Optional ink preconditioning station available
- 1 year warranty parts/6 months labour

### UV Curable Coater Delivers Different Textures and Sheen for Photo Projects

The VersaCoater™ PhotoMate is designed to coat photo projects like portraits, wedding photos, personalized photo albums and other custom photo projects. Capable of processing speeds up to 30m (100 ft.)/ minute, the VersaCoater™ PhotoMate's dual path engineering can create your choice of Smooth, Artisan, Fine Canvas, Linen or Leather textured finishes on the same machine\*. An optional custom proofing roller can also watermark proofs with your shop's logo or other custom watermark.

#### Advanced engineering for a wide range of photo/print applications

Compatible with photo, inkjet and digital presses such as iGen/Indigo/DocuColor/NexPress, the PhotoMate protects and adds value to your clients' photo albums and images. Ideal for silver halide or digitally printed school pictures, wedding portraits, black and white head shots, book covers and virtually anything in between, this compact coater delivers clean, dry prints at high volume and low material cost. Rigid or flexible coated photo paper or other digital media up to 13mm thick (1/2-inch) thick can be coated with the PhotoMate.

#### Built-in versatility

For portrait, wedding or school photo professionals, digital print houses or custom print shops, PhotoMate delivers custom textured as well as smooth UV curable coatings with equal ease. The dual path design plus patented engraved roller system delivers Smooth\*, Artisan, Fine Canvas, Linen, or Leather textures at speeds up to 30mpm (100 fpm); or up to 4500 pages per hour (with optional feeder). The multi tank carousel allows you to switch between different coatings. An optional multi path feature allows you to run two different coatings at the same time.

#### Low cost of ownership

A compact footprint and easy-to-operate features reduce space and staff training costs, making the VersCoater™ PhotoMate a lower cost to own machine than competitors' models. Automated start up and shutdown, semi-automatic cleaning and automatic drain, UV lamp ready monitor and a filtered coating re-circulating system all make operating the PhotoMate efficiently and managing project production easier.

\* The Smooth textured roller comes standard with the VersaCoater™ PhotoMate. Additional textured rollers can be ordered separately.

## TECHNICAL SPECIFICATIONS—VERSACOATER™ PHOTOMATE

### Coating Specifications:

Coating Thickness:	Variable 8 - 14 microns on all models
Coating Technology:	100% UV curable - reverse roll / flood
Process Speed:	10 - 30 metres (30 - 100 ft)/ minute
Coating Roller:	Proprietary
Available Roller Textures:	Smooth (standard). Optional: Artisan, Fine Canvas, Artisan, Linen, Leather and custom watermark proofing roller

### Speed and Dimensions:

	<b>432 mm (17")</b>	<b>610mm (24")</b>	<b>915mm (36")</b>
Max. Coat Width:	432 mm (17")	610mm (24")	915mm (36")
Coater Size: (L x W x H):	1321mm x 787mm x 1168mm (52" x 31" x 46")	1321mm x 990mm x 1168mm (52" x 39" x 46")	2490mm x 1321mm x 1168mm (98" x 52" x 46")
Crated Size (L x W x H):	1702 x 1016 x 1321mm (67 x 40 x 52")	1321 x 1245 x 1168mm (67 x 49 x 52")	1880 x 1626 x 1321mm (74 x 64 x 52")
Coater Net Weight:	276 kg (609 lbs)	417 kg (920 lbs)	635 kg (1400 lbs)
Crated Weight:	381.5 kg (841 lbs)	526 kg (1160 lbs)	794 kg (1750 lbs)

### Electrical Specifications:

Amperage: (Draw/breaker)	25 Amps	30 Amps	50 Amps
Line Voltage:	208-240VAC 50/60Hz 1 ph (does not include cord)		

### Safety and Warranty

Safety Certification:	CE Standards
Emergency Shut Off:	Yes
Ventilation:	External ventilation or air purification highly recommended
Warranty:	1 year parts/6 months labor

### Order Codes

Coater & Curing Unit	VCPHM17R2 (17")	VCPHM24R2 (24")	VCPHM36R2 (36")
Artisan Texture Roller	VCATR17 (17")	VCATR24 (24")	VC-ATR36 (36")
Fine Canvas Texture Roller	VCFCTR17 (17")	VCFCTR24 (24")	VC-FCTR36 (36")
Linen Texture Roll	VCLNTR17 (17")	VC-NTR24 (24")	VC-LNTR36 (36")
Leather Texture Roll	VCLTR17 (17")	VCLTR24 (24")	VC-LTR36 (36")
Proofing Watermark Roller	VCPR17 (17")	VCPR24 (24")	VCPR36 (36")

## INSTACURE UV CURABLE COATINGS

INSTACure Digital Gloss (U.S. Gallon)	ICUVCDG-1G
INSTACure Digital Matte (U.S. Gallon)	ICUVCDM-1G
INSTACure Photo Gloss (U.S. Gallon)	ICUVCPG-1G
INSTACure Photo Lustre (U.S. Gallon)	ICUVVCPPL-1G
INSTACure Photo Matte (U.S. Gallon)	ICUVCPM-1G



TEL: +44 (0)117 958 6500/ 0845 070 0660

ON THE WEB:

[www.drytac.co.uk](http://www.drytac.co.uk)