

WindowTac™—Make any print into a window decal!

Product Description

A visually clear PET film with a permanent adhesive on one side and a removable adhesive on the other. This double sided mounting adhesive is designed for easy, bubble-free face mounting of large graphics to glass or clear acrylic* panels with the aid of a squeegee. 1 mil (23 micron) thick.

Applications

This product has a variety of applications ranging from POP displays, promotional graphics, back-lit display cabinets, shop fronts, and anywhere that requires short term removable face mounted displays.



Directions for use:

1. Clean windows thoroughly with soap and water. A weak solution of 2 drops of soap into 3 quarts (3 litres) of water is ideal. Ensure the surface is completely dry before any application of the product is done.
2. Laminate the permanent adhesive to the face side of the image.
3. Remove the embossed release liner and apply by hand using a squeegee with minimum pressure.
4. The micro grooves imparted into the adhesive layer by the embossed release liner allow the air to evacuate upon installation, giving a bubble-free, easy application.
5. The image can be repositioned up to ten times while retaining the micro grooves in the adhesive.
6. Allow the images to cure for 24 hours for the adhesion to increase.

* If using clear acrylic sheets, ensure that the printed material has been thoroughly cured to reduce the risk of "out gassing".

Technical Properties



Thickness	1 mil (23µ)
Heat resistance range	70° C (158° F)
Peel strength	(20 min, FTM1) 22N/25mm2 (PERM)
Roller Laminator (Not to be used with a Vacuum Press)	
Temperature	Room temperature to 59° -80° F (15-27° C) 40 - 65% humidity
Speed	1ft to 6ft (0.3m to 1.75m)/min
Available Sizes	
PWD25164	25.5" 164' (648mm X 25m)
PWD41164	41" 164' (1041mm X 50m)
PWD51164	51" x 164' (1300mm x 50m)

US TOLL FREE 1-800-280-6013

CANADA TOLL FREE 1-800-353-2883

DRYTAC®

ON THE WEB

www.drytac.com